

# FIREPRO GTX AN

Antistatic Outsole  
Pull On Fire Boot

<b>Standard</b>	ENISO15090:2006	ENISO20345:2004 (+A1:2007)
<b>Category of Protection</b>	F2A H13 P T CI AN	S3 CR HRO SRC WR
<b>Code</b>	FB300GTX	
<b>Size Range</b>	2-15 (UK) • 35-50 (Continental)	
<b>Leg height</b>	34cm	
<b>Upper</b>	2.5 - 2.7mm flame retardant, hydrophobic, waterproof & breathable full grain cow hide leather	
<b>Inner lining</b>	GORE-TEX® Duracom MS Cambrelle 4 Ply seam sealed bootie technology. 100% waterproof & breathable to keep the wearer dry and comfortable at all times	
<b>Soling Technology</b>	Lightweight Dual Density Flame Resistant Rubber soling with antistatic properties along with excellent shock absorption & cushion comfort and heat resistance to 300 °C	
<b>Comfort Features</b>	Padded Top Band	

GORE-TEX® Performance Comfort Footwear System



PSA System

NCR System

DDR Technology

Flex-Z System


ECRC System



White wear indicator incorporated at a depth of 2mm for the user to understand when to replace the boot.

Defined heel breast and ladder grip.

High slip resistant sole unit



**Additional Benefits:** • Reflective Tape  
• Side loop construction for ease of donning